

## THALLOSJET original brand inks for **HP 45**

**Solvent Cyan, Magenta and Yellow** inks are optimized for primary coding and marking on specialty packaging.

It exhibits excellent gamut and durability on wood, varnished cartons, textile and a large variety on non-porous materials.

High print quality and sharp definition. Smear, fade and water resistant.

# Solvent C-M-Y TJSLVCMY01

Optimal Adhesion on Wood  
and non-porous materials

Ink name	<b>Solvent Cyan-Magenta-Yellow</b>
Ink part number	<b>TJSLVCMY01</b>
Cartridge type	<b>HP 45 Si</b>
Target substrates	Wood, Varnished Cartons and non-porous materials
Ink medium	Solvent
Colorant type	Dye
Drop volume	30 pL
Max firing frequency	10 kHz
Jetted ink yield	36 mL
Decap time	Up to 4 hr
Dry time	< 1 sec
Optical density	Substrate dependent
Shelf life	Up to 6 months
Storage condition	10 to 30 °C
Operating condition	10 to 40 °C
Fire pulse voltage	9.4 V
Fire pulse width	1.9 μs
Head warming temperature	Optional

### Cartridge maintenance and handling

Clean the cartridge with lint free cloth moistened with denatured alcohol.

Wipe slowly and gently along the length of the printhead.

### Cartridge storage

Remove cartridge from the printer and apply the cartridge clip over the printhead.

Wipe and purge before use.